






DATA SHEET **HF3-500X**


KEY POINTS


- Ultimate subwoofer
- Featuring "X-guard Technology": control of the driver's cone excursion
- Amazing performance /size/price ratio
- Low distortion: musical bass performances and high acoustical level
- Installation and connections flexibility for Hifi or Home cinema (amplifier /integrated pre-amplifier with or without pre-out exit)
- Wide tuning possibilities: phase inverter, variable frequency cut off, variable slopes:
 24 or 12 dB/oct or LFE mode (for Home cinema use)
- Bass reflex located at the back
- XLR / RCA Inputs
- Dual voltage choice: 110 V / 220 V
- Available in black or white

AUDIO APPLICATIONS

- Hifi or Home Cinema Subwoofer for all Waterfall speakers
- When very high acoustic pressure is required
- Suitable for large rooms: 30 to 60 m² / 320 to 650 ft²







TECHNICAL DETAILS

TYPE	ACTIVE - BASS REFLEX
INTEGRATED AMPLIFIER	500 W / X-GUARD TECHNOLOGY
PEAK POWER	650 W
FREQUENCY RESPONSE (+/- 3 dB)	29 Hz – 150 Hz
PHASE CONTROL	Switch o° / 180°
CROSSOVER FREQUENCIES	VARIABLE 40 TO 150 Hz or LFE Mode
BASS DRIVER	2 X 230 mm / 9" ATOHM LD 230
DIMENSIONS (width x depth x height in mm) (approx. inches)	290 x 490 x 520
WEIGHT Kg / approx. lbs	30 kg / 66 lbs

WATERFALL AUDIO

ZA les praderies - 83 570 Carcès - France waterfallaudio.com

